

PROMATE 6 IRON CURTAIN 2.0 SPECIFICATIONS

Models	Filter & Aeration Tank Size	Media Cu. Ft	(1) Inlet/Outlet	Max. Service Flow GPM	(2) Backwash Rate GPM	Floor Space (WxHxD)
IC-10 PM6.0-IC2.0	10"x54"	1.5	1"	5.0	5.0	26"x68"x16"
IC-10A PM6.0-IC10A-2.0	10"x54"	1.5	1"	5.0	5.0	26"x68"x16"
IC-10+ PM6.0-IC10A-2.0	10"x54"	1.5	1"	5.0	5.0	26"x68"x16"
IC-12 PM6.0-IC12A-2.0	12"x52"	2.0	1"	7.0	8.0	30"x66"x18"
IC-12A PM6.0-IC12A-2.0	12"x52"	2.0	1"	7.0	8.0	30"x66"x18"
IC-12+ PM6.0-IC12A-2.0	12"x52"	2.0	1"	7.0	8.0	30"x66"x18"
IC-13 PM6.0-IC13A-2.0	13"x54"	3.0	1"	8.0	10.0	32"x68"x20"
IC-13A PM6.0-IC13A-2.0	13"x54"	3.0	1"	8.0	10.0	32"x68"x20"
IC-13+ PM6.0-IC13A-2.0	13"x54"	3.0	1"	8.0	10.0	32"x68"x20"

(1) Aeration Head and Check Valve have 1" Inlet/Outlet.

(2) Water temps above 60° F will require a higher backwash rate. Consult factory.